

SPECIFICATIONS

- Epoxy powder-coated iron housing
- Available with threaded connection from M12x1.5 to 4" or with clamp from 1/2" to 5"
- NBR gaskets
- Internal cartridge available in paper or polyester with plastisol or iron caps



CODE	FLOW RATE m ³ /h	R	A	B	C	CARTRIDGE (mm)					
						Mod.	Øo	Øi	H		
MALE GAS THREAD CONNECTIONS						mm					
FSFM12M24	24	M12 x 1.5	M	53	30	10	C7241	38	20	20	51
FSF38GM24	24	G. 3/8"	M	53	30	10	C7241	38	20	20	51
FSF12GM10	10	G. 1/2"	M	79	60	10	C7242	50	23	23	45
FSFM16M10	10	M16 x 1.5	M	79	60	10	C7242	50	23	23	45
FSF34GM36	36	G. 3/4"	M	95	83	40	C6019	64	38	38	69
FSF1GM84	84	G. 1"	M	130	90	60	C4151	98	60	60	70
FSF114GM96	96	G. 1" 1/4	M	130	90	60	C4151	98	60	60	70
FSF112GM210	210	G. 1" 1/2	M	130	115	80	C4563	98	60	60	104
FSF2GM270	270	G. 2"	M	160	135	80	C2827	127	64	64	125
FSF212GM480	480	G. 2" 1/2	M	180	135	80	C2432	150	88	88	125
FSF3GM900	900	G. 3"	M	280	135	80	C2785	212	145	145	163
FSF4GM1350	1350	G. 4"	M	320	210	115	C4285	256	192	192	196
CONNECTIONS WITH CLAMP						mm					
FSF20F30	30	20		95	83	25	C6019	64	38	38	69
FSF40F120	120	40		130	90	25	C4151	98	60	60	70
FSF52F210	210	52		130	115	30	C4563	98	60	60	104
FSF60F270	270	60		160	135	30	C2827	127	64	64	125
FSF70F270	270	70		160	135	30	C2827	127	64	64	125
FSF80F480	480	80		180	135	30	C2432	150	88	88	125
FSF100F900	900	100		280	180	30	C2785	212	145	145	163