

SPECIFICATIONS

- Non-toxic materials
- Average lifetime: approx. 3 months
- Maintenance: none
- Available heights from 4" to 20"
- Filtration: 25 µm

APPLICATIONS

- Pre-filtration and elimination of:
 - odours and taste due to chlorine or other organic compounds
 - reduction of pesticides, insecticides, chlorinated compounds
- Domestic use:
 - for drinking water allowed only with appliances approved by current legislation
 - anti-chlorine treatment for washing machines, showers and other non-potable drinking systems.
- Technical use:
 - anti-chlorine treatment for food, chemical and pharmaceutical industries
 - pre-treatment for the protection of reverse osmosis membranes



Building materials

- Filter medium: Polyester felt
- Inner core: Polypropylene
- Ends and grille: Polypropylene
- Gaskets: PVC
- Treatment material: Granular activated carbon from coconut

Max. operating conditions

- Temperature: 45°C

Height	Dimensions (mm)			Optimum flow rate l/h
	A	B	C	
4"	92	70	30	250
5"	125	70	30	300
7"	173	70	30	450
10"	250	70	30	600
20"	505	70	30	1200



COMPOSITION CODE	CCAg	25	5
	Model	Filtration	Height
		25 = 25 µm	4"
			5"
			7"
			10"
			20"