

MICROGLASS FILTER ROLLS - RFV

Filter stage: **I**
 Filtration class: EN ISO 16890 - (ex EN 779): **G**
 Filter medium: **glass fibre with progressive density**



EFFICIENCY: EUROVENT	80%	82%	55%	88%
FILTRATION CLASS: EN 779	G3	G3	G3	G3
THICKNESS (mm)	1" - 25	2" - 50	3" - 75	4" - 100
MODEL CODE	1	2	3	4

Recommended front speed	m/s	1.5	1.5	1.5	1.5
Recommended end pressure drop	Pa	200	200	200	200
Maximum pressure drop	Pa	350	350	350	350
Initial pressure drop at 2.5 m/s	Pa	30	40	60	80
Temperature	100°C				
Relative humidity	100%				

RFV	MODEL	ROLL HEIGHT (m)	LINEAR METRES
	1	0.5 - 0.6 - 0.75 - 1 - 1.5 - 2	20
	2	0.5 - 0.6 - 0.75 - 1 - 1.5 - 2	20
	3	0.5 - 0.6 - 0.75 - 1 - 1.5 - 2	20
	4	0.5 - 0.6 - 0.75 - 1 - 1.5 - 2	20

Filter composition code

RFV

3

0.75 x 20

Model

Roll Height
x
Linear metres