


SYNTHETIC FIBRE POCKET FILTERS - TFSG

Filter stage: **I**

Filtration class: EN ISO 16890 - (ex EN 779: **G - M**)

Frame: **galvanised steel/plastic profile**

Filter medium: **synthetic fibre fire resistance class F1 DIN 53438**



EFFICIENCY: EUROVENT		35%	45%	55%
FILTRATION CLASS: EN 779		G3	G4	M5
Initial / maximum pressure drop	Pa	100 / 800	120 / 800	160 / 800
Temperature	90°C			

	DIMENSIONS		POCKETS	Q. NOM	SURFACE AREA
	Cod.	mm	n°	m³/h	m²
TFSG	26.15	592x592x360	6	3400	2.6
	5.15	287x592x360	3	1700	1.3
	18.15	490x592x360	5	2550	2.1
	24.15	592x287x360	6	1700	1.3
	4.15	287x287x360	3	850	0.6
	27.15	592x895x360	6	5100	3.9
	6.15	287x895x360	3	2550	1.8
	19.15	490x895x360	5	3800	3.2
	26.19	592x592x500	6	4250	3.6
	5.19	287x592x500	3	2150	1.8
	18.19	490x592x500	5	3200	3.0
	24.19	592x287x500	6	2150	1.8
	4.19	287x287x500	3	1050	0.9
	27.19	592x895x500	6	6400	5.4
	6.19	287x895x500	3	3200	2.7
	19.19	490x895x500	5	4800	4.5
	26.21	592x592x620	6	5300	4.5
	5.21	287x592x620	3	2650	2.3
	18.21	490x592x620	5	4000	3.7
	24.21	592x287x620	6	2650	2.3
4.21	287x287x620	3	1300	1.2	
27.21	592x895x620	6	8000	6.7	
6.21	287x895x620	3	4000	3.4	
19.21	490x895x620	5	6000	5.6	

Filter composition code

TFSG

26.15

6

G4

Dimension Code

No. pockets

Filtration