

Filter stage: **III**
 Filtration class EN 1822: **E - H - U**
 Frame: **anodised extruded aluminium**
 Plenum: **thermoformed plastic with DOP/ Δp probe and diffuser, standard collar \varnothing 250 mm**
 Filter medium: **glass microfibre**
 Sealant: **two-component polyurethane**
 Separators: **thermoplastic**
 Protective screen: **painted aluminium**



EFFICIENCY: EUROVENT	>95%	>99.99%	>99.999%	>99.9999%	
FILTRATION CLASS: EN 1822	E11	H13	H14	U15	
Initial pressure drop	Pa	70	110	120	140
Recommended end pressure drop	Pa	600	600	600	600
Maximum pressure drop	Pa	1000	1000	1000	1000
Temperature	80°C				
Relative humidity	100%				

TCBP	DIMENSIONS		Q. NOM	SURFACE AREA
	Cod.	mm	m ³ /h	m ²
	9.13	305x610x150	300	5.5
31.13	610x610x150	300	5.2	
47.13	1220x610x150	600	11.0	
7.13	300x600x150	600	10.6	
55.13	600x600x150	600	10.0	
46.13	1210x600x150	1200	21.2	
28.13	595x1205x150	1200	20.0	
56.13	297x595x150	300	5.0	
26.13	595x595x150	600	10.0	

Filter composition code

